

ZK4501-8526-xxxx | Motor extension cable 6 mm² with M40 speedtec[®] plug, drag-chain suitable



M40, plug, straight, female, Power: 4+PE, Signal: 4, Data: 2 – M40, socket, straight, male, Power: 4+PE, Signal: 4, Data: 2



Plugs



Electrical data	Head A	Head B
Rated voltage (power)	630 V AC / 850 V DC	630 V AC / 850 V DC
Rated voltage (signal/24V)	150 V AC/DC	150 V AC/DC
Rated current (power)	70 A max.	70 A max.
Rated current (signal/24V)	7 A max.	7 A max.
Rated impulse voltage (power)	6.0 kV	6.0 kV
Rated impulse voltage (signal/24V)	2.5 kV	2.5 kV
Contact resistance	< 5 mΩ (signal), < 1 mΩ (power)	< 5 mΩ (signal), < 1 mΩ (power)
Mechanical data		
Accessories type	Connectors/Cables	Connectors/Cables
Installation size	M40	M40
Connector type	plug	socket
Configuration	straight	straight
Contact type	female	male

Number of positions (face)	Power: 4+PE, Signal: 4, Data: 2	Power: 4+PE, Signal: 4, Data: 2
Wire termination	crimp connection	crimp connection
Mating cycles	500	500
Way of locking	Speedtec®	Speedtec®
Weight per piece	0.450 kg (0.9921 lb)	0.460 kg (1.0141 lb)
Body color	metal	metal
Body material	zinc diecast/nickel plated	zinc diecast/nickel plated
Seal	FKM	FKM
Clamp ring	zinc diecast/nickel plated	zinc diecast/nickel plated
Contact carrier material	PA 6.6 mod., UL 94 V-0	PA 6.6 mod., UL 94 V-0
Contact material	brass/gold plated	brass/gold plated
Environmental data		
Special features	Max. height for operation 2000 m	Max. height for operation 2000 m
Ambient temperature (operation)	-20...+130°C, -4...+266°F	-20...+130°C, -4...+266°F
Protection rating	IP66/67 in screwed condition	IP66/67 in screwed condition
Pollution level	3 (according to VDE 0110/EN61984 part 6.19.2.2)	3 (according to VDE 0110/EN61984 part 6.19.2.2)
Overvoltage category	3 (according to VDE 0110/EN61984 part 6.19.2.2)	3 (according to VDE 0110/EN61984 part 6.19.2.2)

Cable

Electrical data		
Operating voltage	max. 1000 V AC (UL), U ₀ /U 600/1000 V (VDE)	
Insulation resistance	≥ 20 MΩ*km	
Mechanical data		
Cross-section (power)	6 mm ² (approx. AWG10)	
Cross-section (signal)	AWG22 (approx. 0.34 mm ²)	
Cross-section (brake)	1.00 mm ² (approx. AWG18)	
Outer cable diameter	18.0 mm ± 0.4 mm (0.7087" ± 0.0157")	
Min. bending radius, moved in drag-chain	7.5 x outer cable diameter	
Min. bending radius, fixed installation	4 x outer cable diameter	
Weight	540 kg/km (362.826 lb/1000 ft)	
Conductor material	copper bare	
Optical covering factor of shielding	≥ 85%	
Use	drag-chain suitable	
Max. number of cycles	5 million	

Jacket color	orange
Material jacket	PUR (polyurethane)
Wire insulation material	PP (polypropylene)
Printing color	black
Environmental data	
Operation temperature range, moved	-30...+80°C, -22...+176°F
Operation temperature range, fixed installation	-40...+80°C, -40...+176°F
Oil resistance	yes
Flame-retardant	according to IEC 60332-1-2
Halogen-free	yes
Silicone-free	yes

Contact assembly**Dimensions**

A1	100.00 mm
A2	46.00 mm
B1	110.00 mm
B2	45.00 mm

Notes

- Depending on the cable length (L), the following length tolerances apply: $\pm 2-3\%$
- Illustrations similar

- The last three digits of the ordering information is the cable length in decimeters, e.g. ZK4xxx-xxxx-x020 = cable length 2.00 m

Ordering information	Length
ZK4501-8526-xxxx	xxxx = cable length in decimeters
xxxx = 0050	example for 5 m length
sold by the meter, admissible total cable length see documentation of Servo Drive	

Beckhoff®, TwinCAT®, TwinCAT/BSD®, TC/BSD®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2024

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.