


ZK4800-8526-xxxx | Motor connection cable 6 mm² with M40 speedtec[®] plug system, drag- chain suitable



M40, plug, straight, female, Power: 4+PE, Signal: 4, Data: 2 – plug, angled, female, 4-pin – Pitch dimension 3.50 mm, plug, straight, female, 5-pin



Plugs


Electrical data	Head A	Head B	Head C
Rated voltage (power)	630 V AC / 850 V DC	1000 V AC/DC (according to IEC 60664-1, IEC 61984), 600 V (according to UL 1059)	-
Rated voltage (signal/24V)	150 V AC/DC	-	320 V (according to IEC 60664-1, IEC 61984), 300 V (according to UL 1059)
Rated current (power)	70 A max.	70,6 A at 40 °C (according to IEC 60664-1, IEC 61984), 60 A at 40 °C (according to UL 1059)	-
Rated current (signal/24V)	7 A max.	-	10 A at 40 °C (according to IEC 60664-1, IEC 61984), 10 A at 40 °C (according to UL 1059)
Rated impulse voltage (power)	6.0 kV	8.0 kV	-
Rated impulse voltage (signal/24V)	2.5 kV	-	2.5 kV

Contact resistance	< 5 mΩ (signal), < 1 mΩ (power)	4.5 mΩ	< 5 mΩ
Insulation resistance	-	≥ 100 MΩ (according to IEC 60512)	≥ 100 MΩ (according to IEC 60512)
Insulation group	-	I	IIIa
Mechanical data			
Accessories type	Connectors/Cables	Connectors/Cables	Connectors/Cables
Installation size	M40	-	Pitch dimension 3.50 mm
Connector type	plug	plug	plug
Configuration	straight	angled	straight
Contact type	female	female	female
Number of positions (face)	Power: 4+PE, Signal: 4, Data: 2	4-pin	5-pin
Wire termination	crimp connection	Clamping yoke connection	Clamping yoke connection
Recommended torque, screw termination	-	1.2...1.5 Nm	0.2...0.25 Nm
Recommended torque, screw flange	-	0.6 Nm	0.15...0.2 Nm
Mating cycles	500	25	25
Way of locking	Speedtec®	flange and screw	screw
Weight per piece	0.450 kg (0.9921 lb)	0.057 kg (0.1257 lb)	0.004 kg (0.0088 lb)
Body color	metal	black, similar to RAL 9011	black, similar to RAL 9011
Body material	zinc diecast/nickel plated	PA GF, UL 94 V-0	PBT, UL 94 V-0
Seal	FKM	-	-
Clamp ring	zinc diecast/nickel plated	-	-
Contact carrier material	PA 6.6 mod., UL 94 V-0	PA GF, UL 94 V-0	PBT, UL 94 V-0
Contact material	brass/gold plated	copper alloy	copper alloy
Max. wire cross-section	-	AWG22...AWG4	AWG28 ... AWG14 (0.2 mm ² ... 1.5 mm ²)
Environmental data			
Special features	Max. height for operation 2000 m	-	-
Ambient temperature (operation)	-20...+130°C, -4...+266°F	-50...+130°C, -58...+266°F	-50...+100°C, -58...+212°F
Protection rating	IP66/67 in screwed condition	IP20	IP20
Pollution level	3 (according to VDE 0110/EN61984 part 6.19.2.2)	3	3
Overvoltage category	3 (according to VDE 0110/EN61984 part 6.19.2.2)	3	3


Cable

Electrical data	
Operating voltage	max. 1000 V AC (UL), U ₀ /U 600/1000 V (VDE)
Insulation resistance	≥ 20 MΩ*km
Mechanical data	
Cross-section (power)	6 mm ² (approx. AWG10)
Cross-section (signal)	AWG22 (approx. 0.34 mm ²)
Cross-section (brake)	1.00 mm ² (approx. AWG18)
Outer cable diameter	18.0 mm ± 0.4 mm (0.7087" ± 0.0157")
Min. bending radius, moved in drag-chain	7.5 x outer cable diameter
Min. bending radius, fixed installation	4 x outer cable diameter
Weight	540 kg/km (362.826 lb/1000 ft)
Conductor material	copper bare
Optical covering factor of shielding	≥ 85%
Use	drag-chain suitable
Max. number of cycles	5 million
Jacket color	orange
Material jacket	PUR (polyurethane)
Wire insulation material	PP (polypropylene)
Printing color	black
Environmental data	
Operation temperature range, moved	-30...+80°C, -22...+176°F
Operation temperature range, fixed installation	-40...+80°C, -40...+176°F
Oil resistance	yes
Flame-retardant	according to IEC 60332-1-2
Halogen-free	yes
Silicone-free	yes

Contact assembly



Dimensions



A1	100.00 mm
A2	46.00 mm
B1	137.00 mm
B2	52.00 mm
C1	19.00 mm
C2	25.00 mm

Notes

- Depending on the cable length (L), the following length tolerances apply: ± 2-3%
- Illustrations similar
- The last three digits of the ordering information is the cable length in decimeters, e.g. ZK4xxx-xxxx-x020 = cable length 2.00 m

Ordering information	Length
ZK4800-8526-xxxx	xxxx = cable length in decimeters
xxxx = 0050	example for 5 m length
	sold by the meter, admissible total cable length see documentation of Servo Drive

Beckhoff®, TwinCAT®, TwinCAT/BSD®, TC/BSD®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2024

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.